SQTG Leak Check & Regulator Test Kits



The SQTG kits are ideal for bobtail drivers and service personnel that conduct leak check and regulator pressure testing. The SQTG kits contain four pressure gauges:

- a) 30 psi gauge for pressure tap valves in the outlet of a first-stage regulator, or intermediate pressure of an integral two-stage regulator
- b) 300 psi (with high pressure test block) for systems with no regulator pressure taps
- c) 5 psi gauge for testing set and lock up pressure in 2 psi regulators
- d) 35" WC gauge for use in second-stage regulator leak testing

The hose assembly has an inlet swivel connection for attachment to the pressure tap valve The outlet connection is a high pressure (300 psi) industrial quick disconnect coupling for attachment to any of the included gauges.



ISV-A	POL Isolation Valve w/Type A Schrader Test Tap, assembled
ISV-B	POL Isolation Valve w/Type B Test Tap, brass, assembled

SQTG Leak Check & Regulator Test Kits	
Part No.	Description
SQTG4A	Includes: Case with tool tray 1 - QHA hose asssembly 1 - GA30N 30 psi gauge 1 - GA300N 300 psi gauge 1 - GA5N 5 psi gauge 1 - GA5N 57 w.c. gauge 6 - VA1 1/8" NPT x Schrader pressure tap valves 1 - TBA high pressure test block
SQTG4B	Includes: Case with tool tray 1 - QHA hose asssembly 1 - GA30N 30 psi gauge 1 - GA300N 300 psi gauge 1 - GA5N 5 psi gauge 1 - GA35WN 35" w.c. gauge 6 - VB1 1/8" NPT x 1/4" flare pressure tap valves 1 - TBB high pressure test block

