

This universal test kit can be used at any point in the LP system

- At the tank before the first stage regulator (up to 250 psi)
- Between first and second stage regulator (10 psi)
- After the second stage regulator (11" WC)
- Can also be used to check set pressure and lock-up on second stage or line regulator

**SKVB Kit** 

Type B Leak Testing Equipment	
Part No.	Description
SKVB	Type B Universal Test Kit with 0-35" wc tester, POL test block, 12 - 1/8" type B valves, 6 - 1/4" Type B valves, and tool box
KVB Kit	Type B Test Kit with 0-30 PSI Gauge, Hose, & 12 psi regulator
VB1	Type B Test Tap Valve, 1/8" mpt x Type B connection
VB2	Type B Test Tap Vavle, 1/4" mpt x Type B connection
TGB	Type B connection test gauge w/bleeder valve, 0-30 psi gauge
HSB	Type B test adaptor w/ 1/4" fpt for manometer / oz. gauge
ISV-B	POL Isolation Valve with Type B test tap, brass, assembled
ТВВ	MPOL swivel x FPOL brass test block w/VB 1 Flare Test Valve
KR12	Replacement regulator - 1/4" fpt regulator preset at 12 psi
K2-21WC	1 psi regulator, 1/4" fpt
HSB-RS	Replacement buna seal Type B for female test adaptor
The SKVB Kit meets the NFPA 54 requirements for leak check testing	



